

Customer _____ Customer no. _____ Project _____ Date _____

Delivery address _____

Contact _____ Tel. _____ Email _____

MADE TO MEASURE

GENERAL			TYPE OF SONOVENT							PLACEMENT					FLANGE HEIGHT		COLOR			CONTROL						
Reference	Quantity	Total length* (in mm) flanges included	Model / Size	Airlot (in mm)	Position of the thermal bridge	Glass thickness / Flange thickness	Glazing rubber included	Model nose		Glazed-in position	At transom position	Hidden installation / Covered transom			Above	Below	Profiles Mono- color	Profiles Bicolor		End cap and lever	Type	Side		Length control (in mm)		
												Toe out	Toe in	V-measure (in mm)				Naked box	Inside			Outside	Black / White		Manually Cord Rod (134 / 144) Motor	Left Right (seen from the inside)
			XS	10	1	20	Yes No	Standard nose	Flat nose																	
			S	15	2	24																				
			M	20	3	28																				
			L	25	4	32																				
					5	36																				
			XL		6	40																				
						44																				

* Max. 2000 mm (up to 2500 mm for at transom position)

Additional info (ref. on label, remarks, ...)

Customer _____ Customer no. _____ Project _____ Date _____

Delivery address _____

Contact _____ Tel. _____ Email _____

MADE TO MEASURE

GENERAL			SONOVENT COMPACT 75		SONOVENT COMPACT 65				COLOR			CONTROL			OPTION			
Reference	Quantity	Total length* (in mm) flanges included	Glazed-in position	At transom position (by transom profile: ordered separately)	Glazed-in position	At transom position	Covered transom			Naked box (no glass thickness / glass gutter to be specified)	Profiles Monocolor	Profiles Bicolor		End cap and lever	Type	Side	Length control (in mm)	Glazing rubber included
							V74/20	V118/20	V-measure (in mm)			Inside	Outside					
			20	20	20	20												
			24	24	24	24												
			28	28	28	28												
			32	32	32	32												
			36	36	36	36												
			40	40	40	40												
			44	44	44	44												

* Max. 2000 mm (up to 2500 mm for at transom position)

Additional info (ref. on label, remarks, ...)