


FIXSCREEN® GO

SURFACE-MOUNTED, SOLAR & RECESSED

FIXSCREEN® GO



At Renson, we want to help your client find the right shading solution for their project to suit everyone's budget. Therefore we have expanded the Renson Fixscreen range with the Fixscreen Go. The three segments, Fixscreen Go, Fixscreen and Fixscreen Minimal, share the same Renson DNA, but differ from each other in terms of design, product specifications and budget:

Fixscreen Go
Budget-friendly and compact headbox

Fixscreen
The authentic Renson fabric sun protection, since 20 years the reference in the market.

Fixscreen Minimal
Unique design and endless personalisation options

The common Renson DNA

Guaranteed wind resistance up to 130km/h and comprehensive product warranty

Tight fabric surface and long lifespan thanks to Fixscreen- and Smooth-technology

High-quality finish and effortless operation via Renson Solmate

A solution for every window and every budget



Fixscreen® Go IM 1

- Surface-mounted
- Perfect for renovation
- Compact 85 mm x 85 mm headbox that stays within the facade surface
- Simple and fast installation



Fixscreen® Go IM 1 Solar

- Solar powered
- Surface-mounted
- Compact headbox 85 mm x 85 mm that stays within the facade surface
- Simple and fast installation
- No electrical wiring required



Fixscreen® Go IM 7

- Recessed
- Compact headbox 90 mm x 90 mm
- Simple and fast installation
- Two-piece deep (D90 mm x W35 mm) or narrow (D50 mm x W35 mm) guiding channel
- Mounting situation both 'A' and 'B'
- No screws needed when closing the cabinet at the bottom

Design	Fixscreen® Go MS1	Fixscreen® Go Solar	Fixscreen® Go MS7
Head box size (HxD)	85 mm x 85 mm		90 × 90 mm
Square	✓		
Retractable bottom bar	-		
Recessed fabric tube	✓		
Base plate side guiding channel	At an angle of 0°		At an angle of 0° and 5°
Standard Colours	Powder category AT1 / AMG1		
Wind resistance			
Wind classification EN13561:2004	3		
Wind tunnel test report	N° 113-25809		
Guaranteed wind resistance	Up to 130 km/h in closed position		
Product specifications			
Application	Surface-mounted, Solar & Recessed		
Surface	Max. 7,5 m ²		
Smart control via Solmate (Somfy)	✓		
Connect & Go technology	-		
Click & Safe technology	✓		
Control			
Rensonmotor electronic	✓		
Detecto Rensonmotor Safety First	✓		
Somfy, electronic	-		
Rensonmotor radio-controlled	✓		
Rensonmotor radio-controlled Incl. Solarkit	-	✓	-
Somfy, io radio-controlled	✓		
Dimensions			
Fibre glass fabric Sergé & Pricvacy			
Min. Width (Rensonmotor)	730 mm		
Min. Width (Somfy io/Detecto)	650 mm		
Min. Width Solar	-	850 mm	-
Max. Width	3000 mm		
Max. Height	2500 mm		
Max. Surface Area	7,5m ²		
Blackout fibre glass fabric Satiné 21154			
Min. Width	900 mm		
Max. Width	3000 mm		
Max. Height	2500 mm		
Max. Surface Area	7,5m ²		



* L 2 0 0 0 3 0 6 *

All photos shown are for illustration purposes only and are solely an indication of a usage situation. The actual product may vary due to adjustments to the product. Renson reserves the right to make technical modifications to the products shown. The latest brochures can be downloaded from renson.net